

Representative

Catalog Number: ENC1B6N36LANEXRF

**Product ID:** 7TBA127280R0061 **UPC Number:** 78268349724

Status: Active

Pictogram Combination Unit, Unit Type: NEMA-4X & NSF, single face, universal mount, Colour: black, Battery Type: nickel-cadmium, Battery Wattage: 36W, 120/347VAC, Voltage DC: 6V, two lamps, Lamp Type: MR16 LED, Lamp Voltage: 6V, Lamp Wattage: 4W, self-powered, NEXUS wireless system interface, Head Style: shielded, Battery Run Time (Minimum): 30 minutes

- · Certified NSF for use in food processing areas
- Sealed, vandal-resistant faceplate of polycarbonate/split Legend illuminated by longlife white LED's
- Comes standard with two pictogram films per face, for direction selection
- 4-Watt LED emergency lights provide 30 36 feet of egress illumination on a 6-foot wide path
- Remote load capacity: covers with 4-Watt LED lights 100 feet up to 230 feet of egress illumination
- · Comes standard with auto-diagnostic

North American Specifications (UNSPSC)		
UNSPSC	39111707 Combo light unit exit	
IGCC	3938 Combo light unit exit	
Brand Name	Emergi-Lite	
Туре	Pictogram Combination Unit	
Application	Institutional, Industrial, Commercial	
Standard	CSA	
Wattage	36W	
Voltage Rating	120/347VAC, 6VDC	
Battery Runtime	30 minutes	
Battery	Nickel-Cadmium	
Lamp Type	MR16 LED	
Number Of Lamps	2	
Legend	On	
Size	12-5/8 Inches Height x 14 Inches Width	
Material	Polyvinyl / Aluminum	
Mounting	Universal	
Color	Black	
Lamp Wattage	4W	
Pookoging		

Packaging		
Outer Quantity	1	
Outer Dimensions (inches)	1x1x1	
Weight Uom	14 lbs. Each	

## **Documents / Support Tools**

Technical Drawing / Data Sheet Canada Available on Website
Instruction Sheet Available on Website

## For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com