Product data sheet Characteristics

NB230

Circuit breaker, Stab-Lok, 30A, 2 pole, 120/240VAC, 10kA, bolt on mount



Main

| | Range of Product | Stab-lok | |
|--|------------------------------|---------------------------|--|
| | Product or Component Type | Miniature circuit-breaker | |

Complementary

| Line Rated Current | 30 A | |
|--------------------------------|---|--|
| [Ue] rated operational voltage | 120/240 V AC | |
| Mounting Mode | Bolt-on | |
| Poles description | 2P | |
| Breaking capacity | 10 kA | |
| Electrical Connection | Screw connector | |
| AWG gauge | AWG 14AWG 2 aluminium/copper AWG 4AWG 2/0 aluminium/copper | |

Environment

| Product Certifications | CSA |
|------------------------|-----|

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|---------------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.00 in (5.08 cm) |
| Package 1 Width | 3.00 in (7.62 cm) |
| Package 1 Length | 3.50 in (8.89 cm) |
| Package 1 Weight | 9.92 oz (281.227 g) |
| | |

Offer Sustainability

| REACh Regulation | REACh Declaration |
|----------------------------|---------------------------|
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | €Yes |