

ATK

Track Track & Power Feeds

Job Information		
Project Name		Type
Location		
Quantity		Date
Contact/Phone		
Notes		

Features

Extrusion

Constructed of 0.06" extruded aluminum with 0.045" PVC bus bar support holding 12 gauge round bus bars. Polarity groove is located on face of track to indicate location of grounding conductor.

Labels

cULus listed.

Electrical

Single circuit power distribution system designed to supply lighting unit flexibly. Single hot and neutral conductors are rated for max. 20 Amps. Copper electrical conductors are concealed in thermo-plastic, low-profile track section.

Compatibility

Track system is compatible with all A-Line® and Juno® style track fixtures, accessories and connectors.


Mounting

This track is surface mounted using the supplied mounting hardware.



Description

The ATK series is an extruded aluminum track for use with A-Line track fixtures. Available in 2', 4', 6', 8' and 12' nominal length.



Part No.	Length (Excluding end caps)
ATK02	20-1/8" (511mm)
ATK04	44-1/8" (1121mm)
ATK06	68-1/8" (1730mm)
ATK08	92-1/8" (2340mm)
ATK12	140-1/8" (3559mm)



Notes: Accessories should be ordered separately. For additional options please consult your A-Line Lighting representative. Juno is a registered trademark of Juno Lighting Group.

Due to our continued efforts to improve our products, product specifications are subject to change without notice.

Ordering Guide

Length	Colour
ATK [] - []	
02 : 2'	BK : Black
04 : 4'	BN : Brushed Nickel
06 : 6'	WH : White
08 : 8'	
12 : 12'	

Example: ATK04-BN